



<b>Size</b>	Length 6" = 152.4 mm / Diameter 50 mm
<b>Capacity</b>	4000 litres
<b>Filtration</b>	1 µm
<b>Technology</b>	carbon block
<b>Certification</b>	WRAS - NSF (carbon block)
<b>Fitting</b>	JG coupling 1/4"
<b>Flow rate</b>	200 l/h
<b>Pressure</b>	mini 2 bar - maximum 8.6 bar
<b>Temperature</b>	from 4 to 30 °C
<b>Delivery time</b>	3 weeks after order
<b>Conditioning</b>	25 pieces per box
<b>Part number</b>	812325

**BWT water+more label**

Europe's No. 1 in Water Technology

# BWT bestline 6

best water technology

<b>WATER OPTIMISATION</b>		EN
<p>Water treatment system for the removal of chlorine; optimizing the taste and odor of drinking water. Ideal for use with water coolers.</p> <p>Functional in both horizontal and vertical installations. Use only with potable drinking water supplies and for cold water applications! Flush to remove carbon fines, before final connection.</p>	<p><b>Important:</b> Always observe the installation and operation manual provided. Always install in accordance to local plumbing and building codes and regulations.</p> <p>Do not use where water is microbiologically unsafe or of unknown quality without adequate disinfection before or after the unit.</p>	
Nominaldruck/ nominal pressure/ pression nominale/ Pressione nominale, min.-max.:	2-8.6 bar	
Wassertemp./ water temp./ temp. de service/ temperatura acqua, min.-max.:	4-30 °C	
Durchflussgeschwindigkeit/ flow rate/ debit/ scorrimento, max:	200 L/h	
Typ. Kapazität/ capacity/ capacité/ capacità tip.*:	4.000 L*	

\* Filtertausch nach 6 Monaten / Filter replace after 6 months. / Remplacement au bout de 6 mois. / Sostituzione dopo 6 mese.



Vertrieb/Distributor:  
BWT water+more  
www.bwt-wam.com  
PN: FS10A00



4 250266 702347